

```

/*
 * Kirk_F61_Nokia-220-4G.c
 *
 * Initial version created: 2022.01.02 20:00:03
 * Author : Erik, HW details at https://larsenhenneberg.dk/
 * Program for a modified Arduino Nano or a dedicated PCB with an
 * ATmega328P/ATmega168PA to interface electronics to the
 * Kirk F61 rotary dial phone and a Nokia 220 4G LTE mobile phone.
 * 2022.03.06: dialling 050 to power on Nokia, dial 040 to power down
 * 2022.03.14: changed button emulator i/f for button emul. hw v2
 * 2022.03.19: changed synchronization Nokia power on and power off
 * 2022.04.11: improved start up sync. after dialling 050
 * 2022.04.12: added the sleep state for CPU power down
 * 2022.05.22: a bit more specific contents of the "user manual" ;)
 * 2022.06.18: extended timer0 ISR to avoid the 200 msec. ingoing call
 *              input glitch to interrupt the bell ringing intervals.
 * 2022.06.28: extended timer0 ISR to tick the cpu sleep on hook down
 *              and wake up on hook up or on ingoing call
 * 2023.11.02: Using 20 msec timer ticks to provide 25 Hz ringing freq.
 *              to achieve a reliable ringing coil electromagnetic field.
 * 2024.07.15: changes last dial pulse timeout to fit all dial mech. versions

 * User manual:
 * 1: power on the I/F board with ATmega + button emul. board v.2
 * 2: insert the Nokia 220 4G battery
 * 3: power on Nokia: lift hook, dial 050, hook down.. WAIT for approx. 30 sec.
 * 4: ready for ingoing calls or to dial out ( outgoing call at 8 dialled digits )
 * 5: power down Nokia and the ATmega: lift hook, dial 040, hook down
 * 6: lift hook to power up ATmega and WAIT for approx. 30 sec. to start Nokia
 * 7: hook down to continue the state machine from step 4
 */
// Atmega328P, CPU clk 500000Hz: DIV8 fuse set with a 4 MHz x-tal.
// *** fuse settings: EXTENDED=0xFF, HIGH=0xDA, LOW=0x7D
// Timr 0 initialize at startup:
// TCCR0B = 0b0000011; // set prescaler to 64
// OCR0A = 156; // no of counts for 19,968 msec. ~ 20 msec. tmr0 ISR
#define F_CPU 500000

#include <avr/io.h>
#include <stdio.h>
#include <util/delay.h>
#include <avr/interrupt.h>
#include <avr/sleep.h>

void buttonEmulate(uint8_t buttonVal); // Nokia button touch emulation
void buttonSet(uint8_t bVal); // low level Nokia button emulation I/F

void closeCall(void); // close an in-/outgoing call
void powerdownNokia(void); // power down Nokia
void poweronNokia(void); // power on Nokia and sync. to statemachine

void bellsEnable(void); // enable HW signals to the bell ring generator
void bellsDisable(void); // disable HW signals to the bell ring generator

#define ringONtime 1900 // Bell on time in msec
#define ringOFFtime 2300 // Bell off time in msec.
#define hookSleepTime 900000 // Time to CPU sleep after hook down in msec. ( 15 min.)
#define sleepNowTicks hookSleepTime/20 // hook down cpu sleep timer ticks
#define ingoingGlitchTime 240 // ingoing call input glitch time in msec.
#define nokiapausescreentime 10000 // Nokia pause screen timeout value in msec.
#define ringONdefault ringONtime/20 // bell on timer 20 msec ticks
#define ringOFFdefault ringOFFtime/20 // bell off timer 20 msec ticks
#define ingoingGlitchTicksDefault ingoingGlitchTime/20 // ingoing call input glitch 20 msec. ticks

```

```

#define pausescreendefault nokiapausescreentime/20 // Nokia pause screen time 20 msec. ticks
#define dial_timeout_ticks 140/20 // dialling timeout for last dial pulse: 7*20 msec. = 140 msec

#define maxDigits 20 // max phone dial digits
#define touchONperiod 150 // button emulating ON delay in msec.
#define touchOFFmin 250 // button emulating OFF/release delay in msec.
#define phone_no_of_digits 8 // number of phone digits for Denmark inland

#define HOOK PORTD0 // Kirk F61 hook switch port pin
#define RING PORTD1 // Ring gen. enable for Kirk bell coils port pin
#define DIAL PORTD2 // Kirk F61 dial switch port pin (INT0)
#define INGOING PORTD3 // Nokia "vibrator" ingoing call indicator port pin
#define RING25HZ PORTD4 // 31.25 Hz square wave output for ring gen. port pin

// non-dial button emulation values for the button emulator hw v2 decoder
#define ONOFFval 10 // Nokia ON/OFF button emulate value
#define LIFTval 11 // Nokia LIFT button emulate value
#define UNLOCKval 12 // Nokia UNLOCK button emulate value
#define STARval 13 // Nokia * button emulate value
#define GATEval 14 // Nokia # button emulate value

#define Strobe 0x10 // PortC.bit4 = decoder strobe at button emul. hw v2
#define Inhibit 0x20 // PortC.bit5 = decoder inhibit at button emul. hw v2

// pin bit read macros
#define hookPIN (PIND & 0x01) // mask out PORTD0 - HOOK
#define ingoingPIN (PIND & 0x08) // mask out PORTD3 - INGOING

// statemachine emunerations, state names
enum statename {idle, ringing, call_in, call_out, dialling, sleep };
enum statename state = idle;

uint8_t dialled_digits[maxDigits], digit_idx=0;

uint8_t dial_ready = 0, dial_ticks = 0, dialled_number = 0;
uint8_t ring_enable = 0, ringONcnt = ringONdefault, ringOFFcnt = 0;
uint8_t sleepNow = 0, ingoingCall = 0, ingoingGlitchTicks = 0;
uint8_t pausescreenTimeout = 1; // Assume Nokia pause screen timeout at Nokia power on

uint16_t pausescreenCnt = 0; // Nokia pause screen tick timing variable
uint16_t sleepTimer = sleepNowTicks; // cpu sleep tick timing variable

int main(void)
{
    ADCSRA = 0; // disable all ADC subsystems for power saving
    DDRC = 0x3F; // PC0..PC5 as outputs for Nokia 220 4G button emulation
    DDRD = 0x12; // Inputs, except PD1 (RING), PD4 (RING25HZ)

    PORTC = Inhibit; // inhibit button emul. hw decoder
    PORTD &= ~_BV(RING); // disable ring bell power
    PORTD &= ~_BV(RING25HZ); // disable ring gen. interval pin
    PORTD |= _BV(DIAL); // weak pull up at DIAL input

    TCCR0A = 0b00000010; // timer 0 mode 2 - CTC
    TCCR0B = 0b00000011; // set prescaler to 64
    OCR0A = 156; // no of counts for 16 msec. tmr0 ISR
    TIMSK0 = 0b00000010; // trigger interrupt when ctr (TCNT0) >= OCR0A

    EICRA |= (1 << ISC01); // set INT0 to trigger on falling edge
    EIMSK |= (1 << INT0); // Enable INT0 interrupt ( on dial digit )

    EICRA |= (1 << ISC11); // set INT1 to trigger on falling edge
    EIMSK |= (1 << INT1); // Enable INT1 interrupt ( on ingoing call )

```

```
sei();                // Enable interrupts

while(1) //loop forever
{
    switch (state)
    {
        case idle: if (ingoingCall == 1) // if ingoing call detected
                    {
                        state = ringing;
                        bellsEnable();
                    }
                    else
                    {
                        if (hookPIN == 0) // if hook lifted
                        {
                            digit_idx=0; // prepare dialling state
                            dial_ready = 0;
                            dialled_number = 0;
                            state = dialling;
                        }
                    }
                    if (sleepNow == 1) // hook down for enough time for cpu sleep ?
                    {
                        state = sleep;
                    }
                    break;
        case ringing: if (ingoingCall == 0) // if ingoing call unanswered
                      {
                          bellsDisable();
                          state = idle; // back to idle
                      }
                      else
                      {
                          // still ingoing call request
                          if (hookPIN == 0) // if hook lifted, conversation started
                          {
                              buttonEmulate(LIFTval); // emulate hook lift
                              bellsDisable();
                              state = call_in; // continue to call_in
                          }
                      }
                      // during ringing the Nokia screen is active => preset screen timeout
timer
                      pausescreenCnt = pausescreendefault; // preset pause screen
timeout count
                      pausescreenTimeout = 0;
                      break;
        case call_in: // call_in / call_out: close call if hook down and goto idle
        case call_out: if (hookPIN != 0) // if hook down
                       {
                           closeCall();
                           state = idle; // back to idle
                       }
                       break;
        case dialling: if (hookPIN != 0) // if hook down
                       {
                           if (digit_idx != 0)
                           {
                               closeCall();
                           }
                           state = idle; // back to idle
                       }
                       else
                       {
```

```

        if (dial_ready != 0)
        {
            dial_ready = 0;
            buttonEmulate(dialled_number);
            dialled_digits[digit_idx++] = dialled_number;
            dialled_number = 0;
            if (digit_idx == 3)
            {
                if ((dialled_digits[0] == 0) && (dialled_digits[1] == 4)
&& (dialled_digits[2] == 0))
                {
                    while (hookPIN == 0);    // wait for hook down
                    closeCall();
                    powerdownNokia();
                    state = sleep;
                }
                if ((dialled_digits[0] == 0) && (dialled_digits[1] == 5)
&& (dialled_digits[2] == 0))
                {
                    poweronNokia();
                    while (hookPIN == 0);    // wait for hook down
                    state = idle;
                }
            }
            if (digit_idx == phone_no_of_digits)
            {
                buttonEmulate(LIFTval); // button LIFT to call to the
dialled number

                digit_idx = 0;
                state = call_out;
            }
        }
    }

    break;
    case sleep:
        set_sleep_mode(SLEEP_MODE_PWR_DOWN);
        cli();
        PCICR |= 0b00000100;    // turn on bit change interrupt at port D
        PCMSK2 |= 0b00001001;    // turn on pin PCINT16 (hook) and PCINT19 (ingoing)
        sleep_enable();          // sets the SE (sleep enable) bit
        sei();
        sleep_cpu();              // sleep now and.. wake up on PD0 bit change
    // *** HERE the cpu wakes up after call to PCINT2 ISR ( hook lifted ) ***
        sleep_disable();          // deletes the SE bit
        cli();
        sleepNow = 0;             // unflag the cpu sleep timeout flag
        sleepTimer = sleepNowTicks; // reset the cpu sleep timeout counter
        sei();
        state = idle;             // enter the state machine loop after wake up
        break;
    } // switch
} // while
} // main

// closes an in-/outgoing Nokia call: use ON/OFF button, enter lock screen and
// leave lock screen to sync the state machine with the Nokia screen
void closeCall(void)
{
    if (pausescreenTimeout == 1)
    {
        buttonEmulate(ONOFFval);    // Nokia light up from pause screen
    }
    buttonEmulate(ONOFFval);    // Nokia hook down or lock screen
    _delay_ms(900);
}

```

```
    buttonEmulate(ONOFFval);           // make sure to enter lock screen
    _delay_ms(900);
    buttonEmulate(UNLOCKval);          // make sure to enter menu screen
    buttonEmulate(UNLOCKval);          // do unlock screen with
    buttonEmulate(STARval);             // with the * button as well
}

void powerdownNokia(void)
{
    PORTC = ONOFFval + Strobe + Inhibit;
    _delay_ms(1);                      // latching ONOFFval at decoder strobe
    PORTC = ONOFFval + Inhibit;
    _delay_ms(1);
    PORTC = ONOFFval;
    _delay_ms(3000);                   // ON/OFF button emulation delay to close Nokia
    PORTC = ONOFFval + Inhibit;
    _delay_ms(6000);                   // wait for Nokia pause screen
}

void poweronNokia(void)
{
    PORTC = ONOFFval + Strobe + Inhibit;
    _delay_ms(1);                      // latching ONOFFval at decoder strobe
    PORTC = ONOFFval + Inhibit;
    _delay_ms(1);
    PORTC = ONOFFval;
    _delay_ms(6000);                   // ON/OFF button delay to turn on Nokia
    PORTC = ONOFFval + Inhibit;
    _delay_ms(27000);                  // wait for Nokia pause screen timeout
}

void bellsEnable(void)
{
    ringONcnt = ringONdefault; // restart bell on timer
    ringOFFcnt = 0;             // null bell off timer
    PORTD |= _BV(RING);         // enable ring bell power
    ring_enable = 1;            // flag timer0 ISR to ring the bells
}

void bellsDisable(void)
{
    ring_enable = 0;
    PORTD &= ~_BV(RING);        // disable ring bell power
    PORTD &= ~_BV(RING25HZ);    // set ring generator pin low
    ringONcnt = ringONdefault;
    ringOFFcnt = 0;
}

void buttonEmulate(uint8_t buttonVal)
{
    if (pausescreenTimeout == 1) buttonSet(ONOFFval); // wake up the display
    buttonSet(buttonVal);                             // if paused
    pausescreenCnt = pausescreendefault;               // preset pause screen timeout count
    pausescreenTimeout = 0;
}

// set values for button emulation hw v2
void buttonSet(uint8_t bVal)
{
    PORTC = (bVal & 0x0f) + Strobe + Inhibit;
    _delay_ms(1);                      // latching buttonVal at decoder strobe
    PORTC = (bVal & 0x0f) + Inhibit;
    _delay_ms(1);
    PORTC = (bVal & 0x0f);
}
```

```

    _delay_ms(touchONperiod);
    PORTC = (bVal & 0x0f) + Inhibit;
    _delay_ms(touchOFFmin);
}

// Dial interrupt, counts the dial pulses, restarts "last-pulse" time-out
ISR(INT0_vect) {
    if (dial_ready == 0)
    {
        dialled_number++;           // a pulse from dial pulse mechanism might
        dial_ticks = dial_timeout_ticks; // be last -> reset the time-out to:
    }
}

// The 20 msec. timer0 ISR provides the following functions:
// 1. Flags timeout on the cpu sleep time counter
// 2. Check ingoing call input change and the glitch time-out
// 3. Checks if the ring generator signal is to be generated
// 4. generate the 25 Hz bell output in intervals
// 5. Flags timeout on the dial pulse counter
// 6. Flags timeout on the pause screen counter
ISR(TIMER0_COMPA_vect) {
    if (hookPIN == 0) // hook lifted ?
    {
        sleepTimer = sleepNowTicks; // reset sleep cpu timer
    }
    else // hook down
    {
        if ((sleepNow == 0) && (sleepTimer != 0))
        {
            sleepTimer--;
            if (sleepTimer == 0)
            {
                sleepNow = 1; // flag time to cpu sleep
            }
        }
    }
    if (ingoingPIN == 0) // When no ingoing signal
    {
        if (ingoingGlitchTicks != 0) // check ingoing glicth timer
        {
            ingoingGlitchTicks--;
            if ((ingoingGlitchTicks == 0) && (ingoingPIN == 0)) ingoingCall = 0;
            else ingoingCall = 1;
        }
    }
    else ingoingCall = 1;

    if (ring_enable == 1) // Ring bell signal generator enabled ?
    {
        if (ringONcnt != 0) // Check for ongoing ring ON interval
        {
            ringONcnt--;
            if (ringONcnt == 0) // Ring bell ON interval expired ?
            {
                // Yes, bell ON interval has expired
                ringOFFcnt = ringOFFdefault; // restart bell off timer
                PORTD &= ~_BV(RING); // disable ring bell power
                PORTD &= ~_BV(RING25HZ); // set 31.25 Hz ring (bell) gen. port pin low
            }
            else
            {
                // NO:
                if ((half25HZ ^ 0x01) == 0x01) // use 1/2 ringing freq. 31.25 / 2 = 15,625 Hz
                    PORTD ^= _BV(RING25HZ); // toggle 31.25 Hz ring (bell) generator port
            }
        }
    }
}
pin

```

```
    }
}
else
{
    if (ringOFFcnt != 0)                // Check for ongoing ring OFF interval
    {
        ringOFFcnt--;
        if (ringOFFcnt == 0)            // ring bell OFF interval expired ?
        {                               // Yes:
            ringONcnt = ringONdefault;  // restart bell on timer
            PORTD |= _BV(RING);         // enable ring bell power
        }
    }
}

// check time-out on last rotary dial pulse and flag on time-out
if (dial_ticks != 0 )
{
    dial_ticks--;
    if (dial_ticks == 0)
    {
        if (dialled_number == 10) dialled_number = 0;
        dial_ready = 1;
    }
}

// check time-out for the Nokia pause screen
if (pausescreenCnt != 0)
{
    pausescreenCnt--;
    if (pausescreenCnt == 0)
    {
        pausescreenTimeout = 1;
    }
}

}

// invoked on bit change at PD0 ( Kirk F61 hook switch port pin )
// takes place after entering power down mode in state "sleep"
ISR(PCINT2_vect)
{
    PCICR &= ~0b00000100; // turn off bit change interrupt at port D
    PCMSK2 &= ~0b00001001; // turn off pins PD0, PCINT16, PCINT19
}

// invoked on falling edge of port pin input for ingoing calls
ISR (INT1_vect)
{
    ingoingGlitchTicks = ingoingGlitchTicksDefault;
}
```